

New TLE/MF Dry Verge

Product Technical Information Sheet

Minimum roof pitch	Suits the minimum roof pitch of all compatible tiles
Compatibility:	TLE
	Cassius
	Rivius 20/20
Gauge	295 - 345mm
Gauge (with vertical batten installed)	210 - 345mm
Size of Unit	420 x 128 x 44mm
Colours:	Dark Grey/Antique Slate
	Rustic /Flanders
	Tuscan
	Natural Red
	Brown
Primary Fixing (supplied)	35 x 4mm screw
Secondary Eaves Fixing (not supplied)	Minimum 45mm length screw
Box Quantity	50
Material	HIPS

The New TLE/MF Dry Verge System consists of a Standard Unit, Eaves unit and a ridge closure comb. (All products available separately)



BIM Objects Download



Product specification is subject to change and will be updated accordingly.

Before installation please note; The Sandtoft TLE/MF Verge system is not intended to be waterproof. Rainwater running off the roof at the verge will run through the verge units (particularly when used with flat tiles) and drip from the underside of the verge units. Installing each batten and eaves unit correctly will ensure the verge is sufficiently placed away from the gable wall to minimise any staining risks.

The New TLE/MF Dry verge is designed in accordance with BS8612.

For further guidance, download the **New TLE/MF Installation Guide**.

Issue Date: 28/08/2020

Due to different computer monitors/calibrations the images shown may not be an accurate representation of the final products colour.