

Natural Red



Vauban

Interlocking Plain Tile

The Vauban is an interlocking clay tile that gives a clean contemporary look, and can perform down to pitches as low as 22.5°. The Vauban has also been designed to perform as a vertical cladding solution.

Vauban: Interlocking Plain Tile

Features and benefits:

- Over 30% more cost effective than traditional plain tiles
- Interlocking clay tile with easy to lay open gauge
- Natural & colour-permanent clay tile
- Reduces completion times by up to 30%
- Performs at pitches down to 22.5°
- Half the weight of concrete plain tiles & over 40% lighter than clay plain tiles
- Authentic plain tile looks

TECHNICAL DATA	
Minimum roof pitch*	22.5°
Headlap (minimum)	93 mm
Headlap (maximum)	108 mm
Batten spacing at maximum gauge	273mm
Batten spacing at minimum gauge	258 mm
Size of tile	366 x 202 mm
Covering capacity at maximum gauge	21.8 tiles per m ²
Cover width	168 mm
Profile depth	20 mm
Hanging length	326 mm
Weight as laid	47.96 kg per m ²
Weight per 1000	2.2 tonnes
Weight per tile	2.2 kg
Weight per pallet (including pallet & packaging)	0.8 tonnes
Quantity per pallet	350
Battens per m ²	2.7 m
Batten size - up to 450 mm rafter centres	38 x 25mm
Batten size - up to 600 mm rafter centres	50 x 25mm
Nail size/type for tiles	50 x 3.0 mm stainless steel ring shank clout head
Nail size/type for metal tile clips	55 x 3.35mm aluminium ring shank clout head

*For projects where the rafters are below 22.5 degrees an enhanced roof substructure should be installed. Contact Sandtoft Technical Services for advice and a full roof specification. Rafter length restrictions apply at minimum roof pitch. Note: unless otherwise stated, data is based on the tiles laid at minimum headlap. Concealed Vauban tile ventilators must not be used on roof pitches below 22.5 degrees. Please contact Sandtoft Technical Services for further information.

THE RANGE

Vauban Slate Engobe



Vauban Multiblend



Vauban Natural Red



■ Samples available on request

Sandtoft Roof Tiles
 Belton Rd
 Sandtoft
 Doncaster
 DN8 5SY

T 0844 9395 900
F 0844 9395 950
sandtoftorders@wienerberger.com
www.sandtoft.com
www.wienerberger.com